

1108

**CONSTRUCTION & DESIGN**

- Recessed LED downlight
- Constructed in pressure die-cast aluminium alloy and finished in satin white powdercoat paint
- Low profile fixed LED downlight with high lumen output and low glare performance
- Sealed light engine and clear glass diffuser requires no maintenance providing IP44 protection
- Ideal applications in under bench- cupboards, pathways and night light applications.

TECHNICAL PERFORMANCE



- 3W total system power consumption with overload and short circuit protection
- >50,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K colour temperature with low colour shift over time

OPTICAL & THERMAL PERFORMANCE

- Customised housing provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied complete with integral non-dimmable driver
- Comes with power cord and plug
- Clean flat diffuser and trim with no edges - night light
- Power factor > 0.8 with active power factor correction
- Input voltage 220-240V, 50/60 Hz



Weight (kg)	3K						IP44
0.5	CRI >82		45mm				

TOTAL SYSTEM POWER CONSUMPTION = 13W

CODE ORDERING GUIDE: PRODUCT CODE – COLOUR SUFFIX
 Example: 7023-3K-01

WATTAGE	COLOUR TEMPERATURE	 47° BEAM	LUMINAIRE LUMENS
3W	3000K	1108-3-3K	110

SUPPLIED AS STANDARD WITH LEADING & TRAILING EDGE MAINS DIMMABLE DRIVER

TRIM COLOUR OPTION: ADD SUFFIX AFTER THE CODE

-01 Satin White