

1474

PROP



SPECIFICATIONS:



2.4 kg



3K and 4K



5K



Class I



IP44



CE



Available



5 Year warranty



Made in Australia

CONSTRUCTION & DESIGN

- Surface mounted LED fixed downlight
- Constructed in aluminium and finished in durable polyester powdercoat paint
- Fixed LED luminaire has very high lumen output due to the brilliant optical control maintaining an ultra low glare
- Clear tempered glass

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control in various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral driver and terminal block (Refer dimming options table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz





TECHNICAL PERFORMANCE

- 28W, 45W or 60W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with very low colour shift over time

CODE ORDERING GUIDE:


PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1474-SP-3K-28W-01 or 1474-SP-3K-28W/DALI-01


SYSTEM POWER	COLOUR TEMP.	 24° SP	 36° FL	 47° WFL	 55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT			
		PRODUCT CODE					SP	FL	WFL	VWFL
28W	3K	1474-SP-3K-28W	1474-FL-3K-28W	1474-WFL-3K-28W	-	3312	2563	2557	2534	-
	4K	1474-SP-4K-28W	1474-FL-4K-28W	1474-WFL-4K-28W	-	3480	2691	2583	2661	-
	5K	1474-SP-5K-28W	1474-FL-5K-28W	1474-WFL-5K-28W	-	3552	2642	2636	2613	-
45W	3K	1474-SP-3K-45W	1474-FL-3K-45W	1474-WFL-3K-45W	-	5340	3729	3687	3674	-
	4K	1474-SP-4K-45W	1474-FL-4K-45W	1474-WFL-4K-45W	-	5610	3952	3957	3894	-
	5K	1474-SP-5K-45W	1474-FL-5K-45W	1474-WFL-5K-45W	-	6269	3844	3801	3787	-
60W	3K	1474-SP-3K-60W	-	-	1474-VWFL-3K-60W	7605	5740	-	-	5743
	4K	1474-SP-4K-60W	-	-	1474-VWFL-4K-60W	8010	5998	-	-	6108
	5K	1474-SP-5K-60W	-	-	1474-VWFL-5K-60W	8213	5918	-	-	5920

DIM CODE		28W	45W	60W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
/DIM	Leading & Trailing edge	Std	✓	x
	Non-dimmable	x	Std	Std

COLOUR CODE		
-01		Satin White
-06		Matte Black



300



190