

CLEVERTRONICS L10 ULTRABLADE PRO SURFACE MOUNT



PRODUCT INFORMATION

Part Number	LUBPRO-SM
Description	L10 Lithium Nanophosphate Ultrablade Pro surface mount blade Exit, Enabled with Clevertest Plus
Construction	ABS frame with acrylic & PC diffuser
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 360mm x 72mm x 47mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E6.3 C ₉₀ =E6.3
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8002389	PCA:UBP LED strip PCB Assy (CT10602-D1)
8002945	PCA:C/LUBPRO-SM #CT10142-L8 CTP

