

881538 - 100w
881483 - 150w
881537 - 200w

Orbit 2



CONSTRUCTION & DESIGN

- Suspended LED highbay pendant luminaire
- Round new design in high purity die cast aluminium alloy
- Impact resistant polycarbonate semi frosted diffuser
- High performance SMT LED
- Ideal for high ceiling applications like warehouses, factory outlets, retail and architectural spaces

TECHNICAL PERFORMANCE

- 100W, 150W or 200W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watts
- Chromaticity tolerance (MacAdam step) - 2
- Available in 4K and 5K colour temperature with very low colour shift over time
- Working temperature of -30°C to 50°C
- Humidity allowance of 50%-90% RH


OPTICAL & THERMAL PERFORMANCE

- Wide light 120° distribution


ELECTRICAL SYSTEM

- Bolt on, serviceable non-dimmable driver with IP67 protection
- Power factor > 0.93
- Input voltage AC 100-240V, 50/60Hz
- Supplied with two metre flex and plug
- Supplied without chain or wire suspension


881538 - 100w



881483 - 150w



881537 - 200w




Driver with IP67 protection

Weight (kg)	5K						
8.0	CRI >85		SELV		CE	IK08	IP65

TOTAL SYSTEM POWER CONSUMPTION = 100W / 150W / 200W

CODE ORDERING GUIDE: PRODUCT CODE – COLOUR SUFFIX

Example: 881483-4K-05

WATTAGE	COLOUR TEMPERATURE	 120° VERY WIDE	Luminaire Lumens
		PRODUCT CODES	
100W	4K	881538-4K	11922
	5K	881538-5K	12522
150W	4K	881483-4K	18189
	5K	881483-5K	18789
200W	4K	881537-4K	25455

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

-05  Black

MODEL OPTIONS: TO BE SOLD SEPARATELY

483 SURFACE MOUNT BRACKET

