

1320

MODA



SPECIFICATIONS:

0.6 kg	82+ 3K and 4K	70+ 5K	Class I	IP44	CE	5 Year warranty	Made in Australia
--------	------------------	-----------	---------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Surface mounted LED fixed downlight
- Constructed in machined aluminium alloy without visible fasteners
- Finished in durable polyester powder-coat paint
- Acrylic diffuser for a symmetrical low glare diffused illumination

OPTICAL & THERMAL PERFORMANCE

- Efficient optical design and thermal management provides premium optical and thermal performance
- Wide beam distribution with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge mains dimmable driver and terminal block
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 8W or 13W total system power consumption with overload and short circuit protection
- >75,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE:

PRODUCT CODE - COLOUR CODE

Example: 1320-3K-8W-01

SYSTEM POWER	COLOUR TEMP.	110° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		110°
8W	3K	1320-3K-8W	828	617
	4K	1320-4K-8W	870	649
	5K	1320-5K-8W	845	636
13W	3K	1320-3K-13W	1519	1009
	4K	1320-4K-13W	1607	1063
	5K	1320-5K-13W	1568	1041

COLOUR CODE

-01		Satin White
-06		Matte Black



65

Ø170

