

1054

## LUMINA G2



## SPECIFICATIONS:

1.5 kg	82+ 3k and 4k	70+ 5K	Rot 315°	Tilt 120°	Class I	IP65	CE	5 Year warranty	Made in Australia
--------	------------------	-----------	----------	-----------	---------	------	----	--------------------	-------------------

## CONSTRUCTION &amp; DESIGN

- Outdoor LED adjustable floodlight
- Constructed in pressure die cast aluminium alloy with durable powder-coat paint finish
- Heavy duty bracket and lock adjustable mechanism with swivel range of 240°
- Pure aluminium reflector with symmetrical wide beam distribution and low glare illumination
- Heavy duty bracket and lock adjustable mechanism with swivel range of 240°
- Clear tempered glass lens with silicone seals and stainless steel exposed fasteners provide IP54 protection

## OPTICAL &amp; THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control various beam angles with no harsh cut off and ultra low glare

## ELECTRICAL SYSTEM

- Supplied standard with an integral driver and terminal block (refer to dimming option table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

## TECHNICAL PERFORMANCE

- 28W, 35W or 42W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ and Green Wall LED is available upon request

## CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1348-SP-3K-20W-07 or 1348-SP-3K-20W/DALI-07

SYSTEM POWER	COLOUR TEMP.	13° VNSP	23° SP	55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT		
		PRODUCT CODE				VWFL	VNSP	SP
28W	3K	1054-VNSP-3K-28W	1054-SP-3K-28W	1054-VWFL-3K-28W	3213	2543	2604	2570
	4K	1054-VNSP-4K-28W	1054-SP-4K-28W	1054-VWFL-4K-28W	3380	2759	2825	2788
	5K	1054-VNSP-5K-28W	1054-SP-5K-28W	1054-VWFL-5K-28W	3319	2593	2655	2621
35W	3K	1054-VNSP-3K-35W	1054-SP-3K-35W	1054-VWFL-3K-35W	4180	3259	3365	3280
	4K	1054-VNSP-4K-35W	1054-SP-4K-35W	1054-VWFL-4K-35W	4424	3535	3650	3559
42W	3K	1054-VNSP-3K-42W	1054-SP-3K-42W	1054-VWFL-3K-42W	4532	3629	3707	3624
	4K	1054-VNSP-4K-42W	1054-SP-4K-42W	1054-VWFL-4K-42W	4828	3937	4022	3932

DIM CODE	OPTIONS	20W	28W	35W	42W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓	✓
/AD	Analogue Dimming 1-10V	×	×	×	×
/DIM	Leading & Trailing edge	Std	Std	×	×
	Non-Dimmable	×	×	Std	Std

COLOUR CODE	
-07	Textured Black
-11	Textured Silver

