

**LEGEND**

- ELECTRICAL SERVICES SWITCHBOARD.
- SWITCHBOARD / CONTROL PANEL NOT PROVIDED AS PART OF THE ELECTRICAL SUBCONTRACT.
- SINGLE POWER OUTLET.
- DOUBLE POWER OUTLET.
- SPECIAL PURPOSE POWER OUTLET.
- SINGLE PHASE ISOLATOR.
- THREE PHASE ISOLATOR.
- SIGN CONNECTION.
- SPX: LIGHTING CONTROL SWITCH PANEL, TYPE AS NOTED.
- ONE-WAY LIGHT SWITCH.
- TWO-WAY LIGHT SWITCH.
- FAN CONTROLLER.
- CIRCUIT LINE.
- SWITCH LINE.
- DB-x - Py: POWER CIRCUIT DESIGNATION. DENOTES DB AND CIRCUIT.
- xx: LIGHTING CONTROL CHANNEL REFERENCE.
- ELECTRICAL EQUIPMENT AS NOTED.
- ▼: RJ45 COMMUNICATIONS OUTLET.
- ▾: RJ45 GAMING LINK OUTLET.
- GF: GAMING FIBRE.
- FIP: FIRE INDICATOR PANEL.
- : FIRE ALARM SYSTEM DOOR INTERFACE.
- ☒: FIRE ALARM SMOKE DETECTOR.
- ☐: FIRE ALARM THERMAL DETECTOR.
- ☎: RECESSED FIRE ALARM SPEAKER.
- ☎: SURFACE MOUNTED BLACK FIRE ALARM SPEAKER.
- FUSE.
- SINGLE PHASE.
- THREE PHASE.
- △: CURRENT TRANSFORMER C/W REMOVABLE LINK.
- ☎: FUSE LINK.
- ☎: COMBINED FUSE SWITCH.
- ☎: CIRCUIT BREAKER.
- ☎: ISOLATOR.
- ☎: RESIDUAL CURRENT DEVICE.
- ☎: CONTACTOR - NORMALLY OPEN.
- ☎: CONTACTOR - NORMALLY CLOSED.

**LEGEND**

- REFER TO DETAIL NOTED FOR THE AREA SHOWN HATCHED. ADDITIONAL OUTLETS & FITTINGS MAY BE SHOWN ON DETAIL.
- E1: GENERAL LED EMERGENCY LIGHT, RECESSED, WHITE.
- E2: GENERAL LED EMERGENCY LIGHT, MOUNTED IN A CUSTOM MDF BOX, WHITE.
- E3: GENERAL LED EMERGENCY LIGHT, SURFACE MOUNTED BLACK.
- EX: WHITE EMERGENCY LED EXIT LIGHT, FRONT OF HOUSE.
- Lx: LIGHT FITTING C/W NON-MAINTAINED EMERGENCY BATTERY PACK. TYPE AS NOTED.
- L1: RECESSED 300 x 600 FLAT PANEL TROFFER, WHITE.
- L2: CEILING MOUNTED MOVING HEAD COLOUR WHEEL, BLACK.
- L3: 1200 LONG SURFACE IP65 BATTEN, LIGHT GREY.
- L4: EXISTING CARPARK POLE LIGHT TO BE MODIFIED.
- L5: NEW CARPARK POLE UTILISING A MODIFIED L4 FITTING.
- L6: NEW TWIN CARPARK POLE LIGHT TO MATCH EXISTING ADJACENT TWIN POLE LIGHT.
- RDL1: Recessed Downlight, White.
- RDL2: Recessed Downlight, White.
- RDL3: Recessed Downlight, White.
- RDL4: Recessed Downlight, Black.
- RDL5: Recessed Downlight.
- RDL6: Adjustable Recessed Downlight, Non-Dimmed.
- SDL1: Surface Mounted Cylinder Shade C/W Bubble Glass.
- SDL2: Surface Mounted Can Downlight, White.
- SDL3: Surface Mounted Spot Light.
- SDL4: Surface Mounted 800DIA Ball Light.
- SDL5: NO LONGER REQUIRED.
- SDL6: Surface Mounted Adjustable Spot Light, White.
- SDL7: Surface Mounted Can Downlight, Black.
- SDL8: Surface Can Downlight, Black.
- SDL9: Surface Adjustable Spotlight, Black.
- WL1: Wall Light, White.
- WL2: Wall Light, Brass.
- WL3: Wall Light, Brass.
- WL4: Adjustable Wall Mounted Spot Light, Black.
- PL1: Decorative Suspended Pendant.
- PL2: Decorative Suspended Pendant.
- CAT: CATENARY FESTOON LIGHTS WITH STAINLESS STEEL SUPPORT SYSTEM.
- UP1: GARDEN STAKE UPLIGHT FITTING, BLACK.
- UP2: SIGNAGE INGROUND UPLIGHT FITTING.

**LEGEND**

- H1: LINEAR HEAT LAMP.
- H2: LINEAR HEAT LAMP.
- H3: HANGING HEAT LAMP.
- HE/W: CEILING BULKHEAD MOUNTED LINEAR HEATER.
- CF1: 2180 DIA CEILING FAN, WHITE.
- CF2: 1400 DIA CEILING FAN, WHITE.
- Sx: LED STRIP LIGHT, TYPE AS NOTED.
- TRK1: LIGHTING TRACK WITH LIGHTS AS SHOWN.
- HLC: HEAT LAMP CONTROL STATION.

**NOTE**

ALL ELECTRICAL PENETRATIONS THROUGH THE ROOF SHEETING ARE TO BE IN LINE WITH THE STRUCTURAL OR MECHANICAL SERVICES PENETRATIONS TO AVOID DEDICATED FLASHINGS FOR THE ELECTRICAL SERVICES.