

1440

MODLINK



SPECIFICATIONS:

0.4 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	125	SELV	IP44	CE	Available	5 Year warranty	Made in Australia
--------	----------------------	---------------	-----	------	------	----	-----------	--------------------	-------------------

CONSTRUCTION & DESIGN

- Recessed LED downlight constructed in spun aluminium and finished in durable polyester powder-coat paint, anodised gold, anodised silver, or specular aluminium finish
- Deep conical housing provides low glare illumination
- Designed with minimal trim width and thickness to visually integrate within planar ceilings
- Clear tempered glass

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare
- Complies thermally with IC-4 and IC-F classification in accordance with AS/NZS 60598 (13W product only)

ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver (refer to dimming options table)
- All drivers come with quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz




TECHNICAL PERFORMANCE

- 13W, 22W or 28W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE:


PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1440-SP-3K-13W-01 or 1440-SP-3K-13W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 24° SP	 36° FL	 55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT		
		PRODUCT CODE				SP	FL	VWFL
13W	3K	1440-SP-3K-13W	1440-FL-3K-13W	1440-VWFL-3K-13W	1589	1387	1391	1366
	4K	1440-SP-4K-13W	1440-FL-4K-13W	1440-VWFL-4K-13W	1760	1552	1556	1528
	5K	1440-SP-5K-13W	1440-FL-5K-13W	1440-VWFL-5K-13W	1578	1392	1397	1371
22W	3K	1440-SP-3K-22W	1440-FL-3K-22W	1440-VWFL-3K-22W	2533	2170	2171	2144
	4K	1440-SP-4K-22W	1440-FL-4K-22W	1440-VWFL-4K-22W	2814	2427	2428	2398
	5K	1440-SP-5K-22W	1440-FL-5K-22W	1440-VWFL-5K-22W	2519	2178	2179	2152
28W	3K	1440-SP-3K-28W	1440-FL-3K-28W	1440-VWFL-3K-28W	3430	2725	2752	2701
	4K	1440-SP-4K-28W	1440-FL-4K-28W	1440-VWFL-4K-28W	3752	2982	3012	2955
	5K	1440-SP-5K-28W	1440-FL-5K-28W	1440-VWFL-5K-28W	3476	2732	2761	2710

DIM CODE	OPTIONS	13W	22W	28W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
/DIM	Leading & Trailing edge	Std	Std	Std
	Non-dimmable	x	x	x

COLOUR CODE		
-01		Satin White
-06		Matte Black
-13		Anodised Silver
-26		Anodised Gold
-30		Specular Aluminium



OVERALL VIEW

