

1412

SOLO



SPECIFICATIONS:



0.5 kg



3K and 4K



5K



Class I



IP44



Available



5 Year warranty



Made in Australia

CONSTRUCTION & DESIGN

- Surface mounted LED fixed downlight
- Constructed in machined aluminium
- Finished in durable polyester powder-coat paint
- Clear tempered glass

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge mains dimmable driver and terminal block
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 8W or 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE:

PRODUCT CODE

COLOUR CODE

Example: 1412-3K-8W-01

| SYSTEM POWER | COLOUR TEMP. | 50° BEAM ANGLE | HOT LED LUMENS | LUMINAIRE LUMEN OUTPUT |
|--------------|--------------|----------------|----------------|------------------------|
| | | PRODUCT CODE | | 50° |
| 8W | 3K | 1412-3K-8W | 914 | 737 |
| | 4K | 1412-4K-8W | 947 | 765 |
| | 5K | 1412-5K-8W | 851 | 693 |
| 13W | 3K | 1412-3K-13W | 1589 | 1210 |
| | 4K | 1412-4K-13W | 1760 | 1352 |
| | 5K | 1412-5K-13W | 1578 | 1212 |

| DIM CODE | OPTIONS | 8W | 13W |
|----------|---------------------------|-----|-----|
| /DALI | Dali Dimming / Switch Dim | ✓ | ✓ |
| /DSI | Digital Dimming | x | x |
| /AD | Analogue Dimming 1-10V | x | x |
| /DIM | Leading & Trailing edge | Std | Std |

COLOUR CODE

-01




Satin White

-06



Matte Black



145

Ø115

