

## 1057-2L RIGA 2



## SPECIFICATIONS:

0.7 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	108x210	Rot 355°	Tilt 35°	SELV	IP40	CE	Available	Oval Beam Available	5 Year warranty	Made in Australia
--------	----------------------	---------------	---------	----------	----------	------	------	----	-----------	---------------------	--------------------	-------------------

## CONSTRUCTION &amp; DESIGN

- Recessed LED adjustable downlight
- Housing and trim is constructed in steel and die cast aluminium and finished in durable polyester powder-coat paint
- Recessed matte black housing creating a dynamic visual impact with low glare lighting performance
- Gimble and rotatable rings gives directional flexibility for both ambient and feature lighting
- Available in multiple downlights with independent aiming from one fixture
- Clear tempered glass

## OPTICAL &amp; THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare
- Compatible with an Oval Beam Lens (Datasheet Available upon Request)

## ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver (refer to dimming options table)
- All drivers come with quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz

## TECHNICAL PERFORMANCE

- 2x8W, 2x12W, 2x13W or 2x22W total system power consumption with overload and short circuit protection
- > 65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request


## CODE ORDERING GUIDE:






PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1057-2L-VNSP-3K-8W-01 or 1057-2L-VNSP-3K-8W/DALI-01

DIM CODE	OPTIONS	2x8W	2x12W	2x13W	2x22W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	x	✓	✓
/DIM	Leading & Trailing edge	Std	Std	Std	Std

COLOUR CODE	Trim colour (internal is always black)
-01	Satin White
-06	Matte Black
-10	Bright Silver



SYSTEM POWER	COLOUR TEMP.		14° VNSP		24° SP		36° FL		47° WFL		55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT				
		PRODUCT CODE											VNSP	FL	WFL	WFL	VWFL
2x8W	3K	1057-2L-VNSP-3K-8W	1057-2L-SP-3K-8W	1057-2L-FL-3K-8W	1057-2L-WFL-3K-8W	-	914	806	831	839	835	-					
	4K	1057-2L-VNSP-4K-8W	1057-2L-SP-4K-8W	1057-2L-FL-4K-8W	1057-2L-WFL-4K-8W	-	947	840	865	869	864	-					
	5K	1057-2L-VNSP-5K-8W	1057-2L-SP-5K-8W	1057-2L-FL-5K-8W	1057-2L-WFL-5K-8W	-	851	759	784	788	783	-					
2x12W	3K	1057-2L-VNSP-3K-12W	-	-	-	-	1270	1092	-	-	-	-					
	4K	1057-2L-VNSP-4K-12W	-	-	-	-	1320	1134	-	-	-	-					
	5K	1057-2L-VNSP-5K-12W	-	-	-	-	1197	1028	-	-	-	-					
2x13W	3K	-	1057-2L-SP-3K-13W	1057-2L-FL-3K-13W	-	1057-2L-VWFL-3K-13W	1589	-	1362	1370	-	1337					
	4K	-	1057-2L-SP-4K-13W	1057-2L-FL-4K-13W	-	1057-2L-VWFL-4K-13W	1760	-	1524	1531	-	1451					
	5K	-	1057-2L-SP-5K-13W	1057-2L-FL-5K-13W	-	1057-2L-VWFL-5K-13W	1578	-	1365	1376	-	1300					
2x22W	3K	-	1057-2L-SP-3K-22W	1057-2L-FL-3K-22W	-	1057-2L-VWFL-3K-22W	2533	-	2121	2133	-	2065					
	4K	-	1057-2L-SP-4K-22W	1057-2L-FL-4K-22W	-	1057-2L-VWFL-4K-22W	2814	-	2379	2389	-	2252					
	5K	-	1057-2L-SP-5K-22W	1057-2L-FL-5K-22W	-	1057-2L-VWFL-5K-22W	2519	-	2123	2139	-	2023					