

SL6391 PILLAR LED WALL DOWNWARD LUMINAIRE

Superlight SL6391 is a premium architectural LED wall luminaire, meticulously crafted for both indoor and outdoor applications. Constructed from solid 316 marine-grade stainless steel, it embodies durability and refined aesthetics. Featuring high-output integrated LED modules and an internal LED driver, the SL6391 is ideal for enhancing exterior facades, passageways, and architectural wall lighting with seamless, energy-efficient illumination.

SPECIFICATIONS

Input Voltage:	110-240VAC
Power Consumption:	7W
Fitting Height Dimension:	85mm
Body Diameter:	68mm
Mounting Base Dimension:	75mm
LED Classification:	High Power CREE XPE2
LED Driver Configuration:	Integral, Constant Current
Typical Light Source Efficacy:	85lm/W
Standard Beam Angle:	40°
Fixture Material:	316 Marine Grade Stainless Steel
Standard Colour/Finishes:	Powdercoated / Brushed Stainless
Recommended Ambient Temp:	-15 ~ +45°C
IP Protection Rating:	IP65

PHOTOMETRIC INFORMATION

SL6391-15		1x40° CCT: 6000K CRI: >85
SL6391-17		1x40° CCT: 4000K CRI: >85
SL6391-21		1x40° CCT: 3000K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Landscape & garden lighting, Bars, hotels & hospitality projects, Commercial fitouts, Residential lighting, Task lighting. Residential lighting projects, landscape lighting, interior and exterior wall lighting.

CONTROL & DIMMING COMPATIBILITY

SL6391 is usually supplied with non dimmable.
Optional dimmable configurations including Phase Dim, DALI, 1-10V, DMX512.
Wireless Casambi control option also available by request.
Dimming and control options may require remote mounted LED Driver.
Please contact us for options and availability.

ORDERING INFORMATION

SL6391-21	Superlight Wall Mounted Down Luminaire 3000K
SL6391-17	Superlight Wall Mounted Down Luminaire 4000K
SL6391-15	Superlight Wall Mounted Down Luminaire 6000K

CUSTOMISATION OPTIONS

Fixture colour can be powdercoated or refinished by request
12VDC version available by special request
Custom LED power options can be configured by request
Dimmable options available by special request
**Custom options may be subject to minimum order quantities

CASAMBI



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

