

1573

MOLO



UNIQUE SQUARE
DOUBLE BATWING
LIGHT OUTPUT

SPECIFICATIONS:

One way	6.1 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	Class I	IP65	CE	5 Year warranty	Made in Australia
---------	--------	----------------------	---------------	---------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Surface mounted LED exterior wall light for up or down illumination
- Housing constructed in pressure die cast aluminium alloy and finished in durable powder-coat paint
- Robust housing for superior durability
- Wall cable gland power entry
- Clear tempered glass cover, and silicone gaskets provides IP65 weather protection
- Can be used as up or downlight

OPTICAL & THERMAL PERFORMANCE

- LED thermal management incorporates both conduction and natural convection to transfer heat rapidly away from LED source to achieve maximum life of LED
- High efficiency optics for brilliant optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral driver (refer to dimming options table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz
- Supplied with 200mm input cable

TECHNICAL PERFORMANCE

- 28W, 45W or 52W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE:


PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1573-3K-28W-03 or 1573-3K-28W/DALI-03

SYSTEM POWER	COLOUR TEMP.	65x65° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		65x65°
28W	3K	1573-3K-28W	4175	3709
	4K	1573-4K-28W	4327	3976
	5K	1573-5K-28W	4340	3931
45W	3K	1573-3K-45W	6068	5256
	4K	1573-4K-45W	6337	5634
	5K	1573-5K-45W	6326	5569
52W	3K	1573-3K-52W	7457	6572
	4K	1573-4K-52W	7788	7045
	5K	1573-5K-52W	7819	6965

DIM CODE	OPTIONS	28W	45W	52W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	x	x
/DIM	Leading & Trailing edge	Std	✓	x
	Non-dimmable	x	Std	Std

COLOUR CODE	
-03	Textured White
-07	Textured Black
-11	Textured Silver



ALTERNATIVE MOUNTING

