

1321

JUTE

1322



## SPECIFICATIONS:

2.4 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	Class I	IP54	CE	5 Year warranty	Made in Australia
--------	----------------------	---------------	---------	------	----	--------------------	-------------------

## CONSTRUCTION &amp; DESIGN

- Surface mounted LED downlight
- Constructed in aluminium and finished in durable polyester powder-coat paint
- Fixed high lumen output luminaire with regressed LED position providing low glare illumination
- Clear tempered glass providing IP54 protection

## OPTICAL &amp; THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare
- Reflector is available in special matte lustre white treatment, allowing wider beam angle while maintaining excellent luminaire lumen output

## ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge mains dimmable driver and terminal block, also compatible with a range of dimming systems
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz



## TECHNICAL PERFORMANCE

- 22W or 28W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

## CODE ORDERING GUIDE:



PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1321-3K-22W-01 or 1321-WR-3K-22W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 27° STD REFLECTOR	 81° WHITE REFLECTOR	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT	
		PRODUCT CODE			27°	81°
22W	3K	1321-3K-22W	1321-WR-3K-22W	2666	2204	2181
	4K	1321-4K-22W	1321-WR-4K-22W	2805	2449	2427
	5K	1321-5K-22W	1321-WR-5K-22W	2506	1842	1825
28W	3K	1322-3K-28W	1322-WR-3K-28W	3676	2864	2818
	4K	1322-4K-28W	1322-WR-4K-28W	3813	3055	3025
	5K	1322-5K-28W	1322-WR-5K-28W	3319	2546	2521

DIM CODE	OPTIONS	22W	28W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
/DIM	Leading & Trailing edge	Std	Std

COLOUR CODE	
-01	Satin White
-06	Matte Black



## WHITE REFLECTOR OVERVIEW

