

1069

MINI AURA



SPECIFICATIONS:

1.9 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	Tilt 15°	Class I	IP67	CE	5 Year warranty	Made in Australia
--------	----------------------	---------------	----------	---------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Inground LED tilt adjustable exterior uplighter
- Trim constructed in cast AISI 316 brushed stainless steel and body constructed in AISI 304 stainless steel and finished in black powder-coat paint
- 10mm clear toughened cool touch glass and durable silicone seals providing IP67 protection
- Plastic installation well included with each fitting to facilitate installation and maintenance
- This fitting is not submersible

OPTICAL & THERMAL PERFORMANCE

- Optics and integral heatsink provides premium optical and thermal performance
- Efficient optical control available in various beam angles with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with a integral leading and trailing edge mains dimmable driver (refer to dimming option table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz
- Supplied with 500mm input cable





TECHNICAL PERFORMANCE

- 8W or 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE


Example: 1069-SP-3K-8W-28 or 1069-SP-3K-8W/DALI-28

SYSTEM POWER	COLOUR TEMP.	 24° SP	 36° FL	 47° WFL	 55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT			
		PRODUCT CODE					SP	FL	WFL	VWFL
8W	3K	1069-SP-3K-8W	1069-FL-3K-8W	1069-WFL-3K-8W	-	914	799	802	805	-
	4K	1069-SP-4K-8W	1069-FL-4K-8W	1069-WFL-4K-8W	-	947	830	832	836	-
	5K	1069-SP-5K-8W	1069-FL-5K-8W	1069-WFL-5K-8W	-	851	752	753	756	-
13W	3K	1069-SP-3K-13W	1069-FL-3K-13W	-	1069-VWFL-3K-13W	1589	1315	1307	-	1284
	4K	1069-SP-4K-13W	1069-FL-4K-13W	-	1069-VWFL-4K-13W	1760	1467	1458	-	1436
	5K	1069-SP-5K-13W	1069-FL-5K-13W	-	1069-VWFL-5K-13W	1578	1318	1310	-	1291

INSTALLATION WELL


Installation well included

Nylon plastic well to facilitate installation & maintenance. Supplied with each fitting. Height of plastic well is 243mm and the diameter is 154mm. The luminaire must be mounted with suitable drainage as shown below.



243


Ø154




DIM CODE	OPTIONS	8W	13W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	x	x
/DIM	Leading & Trailing edge	Std	Std

COLOUR CODE

-28	Brushed Stainless Steel
-----	-------------------------



Ø177



200