

# SL800U GUNMETAL LED SPOTLIGHT/PROJECTOR

Superlight Gunmetal series is a professional range of LED lighting fixtures which for use within commercial projects, architectural illumination and landscapes. SL800U features a stylish design, robust construction and adjustable mounting bracket. LED configurations include options up 30W & other configuration options are available.

## SPECIFICATIONS

Series Model Number:	SL800UA-	SL800UD-
Input Voltage:	100-240VAC	24VDC
Power Consumption:	60W/86W	60W/86W
Body Diameter:	220mm	220mm
Body Length:	200mm	200mm
Overall Height:	320mm	320mm
Fixture Material:	Magnesium Alloy	Magnesium Alloy
LED Classification:	CREE XP-E	CREE XP-E
Typical Light Source Efficacy:	90lm/W	90lm/W
Beam Angle Options:	5° / 15° / 30° / 45°	5° / 15° / 30° / 45°
RGB Option:	Int DMX Decoder	Int DMX Decoder
Recommended Ambient Temp:	-15 ~ +55°C	-15 ~ +55°C
IK Impact Protection Rating:	>IK08	>IK08
IP Protection Rating:	IP66	IP66

## PHOTOMETRIC INFORMATION

SL800U**6500K	CCT: 6500K CRI: >85
SL800U**4000K	CCT: 4000K CRI: >85
SL800U**3000K	CCT: 3000K CRI: >85
SL800U**RGB	RGB with DMX

Detailed photometric report and IES files available by request

## TYPICAL APPLICATIONS

Typical applications include landscape and feature lighting, sculptures and flagpole illumination, garden lighting and architectural highlighting.

## CONTROL & DIMMING COMPATIBILITY

Superlight SL800 fittings can be fitted with integral dimming control gear by special request. RGB+DMX configuration available. RGB fitting is supplied with integral DMX decoder.

## ORDERING INFORMATION

SL800U**-3000K	Superlight SL600U LED Landscape Spotlight/Projector
SL800U**-4000K	Superlight SL600U LED Landscape Spotlight/Projector
SL800U**-6500K	Superlight SL600U LED Landscape Spotlight/Projector
SL800U**-RGB	Superlight SL600U LED Landscape Spotlight/Projector

## CUSTOMISATION OPTIONS

- Fixture colour can be refinished
- DALI dimmable options available by special request
- Y-Bracket (yoke) mounting option available by special request
- Vandal resistant protective steel cage available by special request
- Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

