

ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3824a - DUBLIN DOCKS TAVERN, BIGGERA WATERS - BISTRO BAR


C3824a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 25 SEPTEMBER 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
RD01	18W 3000K LED	REPLACE AND RESUPPLY WITH NEW CABLING THE EXISTING RECESSED DOWNLIGHT WITH A NEW 150 DIA RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER	WHITE	RAPID R1352-18-WH-WW-DALI	C
RD02	18W 3000K LED	REPLACE AND RESUPPLY WITH NEW CABLING THE EXISTING RECESSED DOWNLIGHT WITH A NEW 150 DIA RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER	WHITE	RAPID R1352-18-WH-WW-DALI	C
RD03	18W 3000K LED	NEW RECESSED DOWNLIGHT WITH A NEW 150 DIA RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER	WHITE	RAPID R1352-18-WH-WW-DALI	C
RDE	EXISTING RECESSED DOWNLIGHT TO BE REMOVED				A
TL01	25W 3000K LED PER FITTING	REPLACE THE EXISTING SURFACE TRACK AND FITTINGS WITH A NEW TRACK AND NEW FITTINGS AS INDICATED PROVIDE EACH TRACK WITH A REMOTE DALI DIMMABLE DRIVER LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	WHITE	RAPID LED 6 WIRE SURFACE DALI TRACK AND R2582-BK-CW-24-DALI AS NOTED	A
TL02	25W 3000K LED PER FITTING	PROVIDE NEW ADJUSTABLE TRACK MOUNTED FITTINGS ON THE TL01 TRACK TO SUPPLEMENT THE TL01 FITTINGS	WHITE	RAPID LED R2582-BK-CW-24-DALI	A
SLE	EXISTING SURFACE MOUNTED FITTING TO BE REMOVED				A
S1	14.4W/M 2700K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER WITHIN THE CEILING PELMET AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	A
S2	10W/M 2700K LED	IP67 LED FLEX SCREW FIXED BEHIND THE MIRROR AS PER THE ELEVATION AND ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT.	WHITE	RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER	A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3824a - DUBLIN DOCKS TAVERN, BIGGERA WATERS - BISTRO BAR


C3824a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 25 SEPTEMBER 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
S3	10W/M 2700K LED	IP67 LED FLEX SCREW FIXED WITHIN THE BAR COUNTER FRONT AS PER THE ELEVATION AND ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT.	WHITE	RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER	A
S4	14.4W/M 2700K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE CENTRAL BAR COUNTER TOP AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	A
FS01	1W LED AT 500 CENTRES	FESTOON LIGHTS WITH NEW 24V DC IP65 FESTOON LIGHTING TO BE FIXED TO A 316 STAINLESS STEEL WIRE SUPPORT SYSTEM. SUPPLY THE NEW FESTOON LIGHTS VIA REMOTE DALI DIMMABLE DRIVERS IN A CONCEALED ACCESSIBLE POSITIONS NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE LENGTH AND POSITION ON SITE	BLACK CABLE AND FIXINGS 316 STAINLESS STEEL SUPPORT AND FIXINGS	FIRE FLY FC1-50-BL + BL-G45-GW-T	C
BL01	2200K LED	TREE BUD LIGHTS. REMOVE THE EXISTING BUD LIGHTS. PROVIDE A NEW DALI DIMMABLE POWER SUPPLY WITH THE DRIVER LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DRAWINGS.	WHITE	FIREFLY LIGHTING S0-36431	C
PD01	9W TRAILING EDGE DIMMABLE A60 240 VOLT E27 2200K LED LAMP	REPLACE THE EXISTING PENDANT LIGHTS WITH A NEW FITTING AND CABLING. PROVIDE THE NEW FITTING AS A DECORATIVE 570 DIA PENDANT. CONFIRM THE SUSPENSION HEIGHT ON SITE WITH THE ARCHITECT	NATURAL	LIGHTING COLLECTIVE EL0052P WRAPPED RATTAN	A
PD02	9W TRAILING EDGE DIMMABLE A60 240 VOLT E27 2200K LED LAMP	DECORATIVE 850 X 1020 PENDANT. CONFIRM THE SUSPENSION HEIGHT ON SITE WITH THE ARCHITECT	BRASS	LIGHTING COLLECTIVE EML845PL-001 DIAMOND CROCHET WIRE	A
PD03	9W TRAILING EDGE DIMMABLE A60 240 VOLT E27 2200K LED LAMP	DECORATIVE 540 X 610 PENDANT. CONFIRM THE SUSPENSION HEIGHT ON SITE WITH THE ARCHITECT	BRASS	LIGHTING COLLECTIVE EML845PL-001 DIAMOND CROCHET WIRE	A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3824a - DUBLIN DOCKS TAVERN, BIGGERA WATERS - BISTRO BAR


C3824a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 25 SEPTEMBER 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
PD04	9W TRAILING EDGE DIMMABLE A60 240 VOLT E27 2200K LED LAMP	DECORATIVE 1060 X 1060 PENDANT. CONFIRM THE SUSPENSION HEIGHT ON SITE WITH THE ARCHITECT	BRASS	LIGHTING COLLECTIVE EML563PL-001 GEOMETRIC CROCHET WIRE	A
PD05	9W TRAILING EDGE DIMMABLE A60 240 VOLT E27 2200K LED LAMP	DECORATIVE 1510 X 680 PENDANT. CONFIRM THE SUSPENSION HEIGHT ON SITE WITH THE ARCHITECT	BRASS	LIGHTING COLLECTIVE EML562PL-002 ELONGATED CROCHET WIRE	A
PD06	5W TRAILING EDGE DIMMABLE A60 240 VOLT B22 2200K LED LAMP	DECORATIVE 11900 PENDANT. TO REPLACE THE EXISTING POOL TABLE PENDANT.	BLACK	FAT SHACK VINTAGE P275-MB-SML-BLK 3 LIGHT PENDANT CONE	B
WL01	6W TRAILING EDGE DIMMABLE A60 240 VOLT E27 2200K LED LAMP	REPLACE AND RESUPPLY WITH NEW CABLING THE EXISTING DECORATIVE WALL LIGHT MOUNTED WITH A NEW FITTING.	AMBER	FAT SHACK VINTAGE W1315-AMB GAMBIER GLASS	A
HRE		EXISTING HEATER AND ASSOCIATED CONTROLS TO BE RETAINED / REINSTATED.			A
CHANNEL x		CONTROL CHANNEL WITH A NUMERICAL REFERENCE. REFER TO THE POWER AND LIGHTING CONTROL SCHEDULE			A
LIGHTING CONTROL SWITCH PANEL 1 (SP1)		EXISTING LIGHTING CONTROLS TO BE REMOVED.			A
LIGHTING CONTROL SWITCH PANEL 2 (SP2)		EXISTING LIGHTING CONTROLS TO BE REMOVED.			A
LIGHTING CONTROL SWITCH PANEL 3 (SP3)		6-BUTTON PROGRAMMABLE SWITCH PANEL C/W CENTRAL LCD DISPLAY MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	ALUMINIUM	DYNALITE ANTUMBRA DISPLAY	A
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
IP56 SINGLE POWER OUTLET		SINGLE POWER OUTLET IP56 MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	GREY	CLIPSAL 56 SERIES	A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3824a - DUBLIN DOCKS TAVERN, BIGGERA WATERS - BISTRO BAR

C3824a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 25 SEPTEMBER 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
SINGLE-PHASE ISOLATOR		SINGLE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT20	A
THREE-PHASE ISOLATOR		THREE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT. "RSD" DENOTES ROLLER SHUTTER DOOR SUPPLY - COORDINATE LOCATION ONSITE WITH MOTOR.	-	CLIPSAL WHT35	A
SIGN CONNECTION		COORDINATE THE LOCATION AND CONNECTION WITH THE SIGN CONTRACTOR ENSURING THE CONNECTION ARE PROVIDED WITH APPROPRIATE WEATHER PROTECTION AND ARE CONCEALED FROM VIEW.			A
MSB		EXISTING MAIN SWITCHBOARD TO REMAIN. UNDERTAKE THE REPAIRS AND MODIFICATIONS TO THE MSB AS PER THE NOTES. PROVIDE AN ELECTRONIC PHOTOGRAPH OF EACH COMPLETED REPAIR.			A
MSSB		EXISTING MECHANICAL SERVICES SWITCHBOARD TO REMAIN.			A
DB-B		NEW DISTRIBUTION BOARD DB-B REFER TO THE NOTES AND DISTRIBUTION BOARD DB-B SCHEDULE FOR ADDITIONAL INFORMATION AND REQUIREMENTS. PROVIDE DB-B WITH A 4C+E 35mm SUBMAIN FROM A NEW 63A MCB IN DB-G. PROVIDE A SHOP DRAWING OF THE DB FOR APPROVAL INCLUDING ALL LIGHTING CONTROLS AS PART OF THE SHOP DRAWING.			A
DB-G		EXISTING DISTRIBUTION BOARD TO REMAIN. UNDERTAKE THE REPAIRS AND MODIFICATIONS TO DB-G AS PER THE NOTES. PROVIDE AN ELECTRONIC PHOTOGRAPH OF EACH COMPLETED REPAIR. PROVIDE DB-G WITH A 63A THREE PHASE MCB TO SUPPLY THE NEW DB-B VIA A NEW CONCEALED 4C+E 35mm SUBMAIN.			A